







Mark lanes, hazards and safety areas. Faster than masking and painting!

3M[™] Safety Stripe Tape Black/Yellow 5702

(UPC: 00-021200-04585-1) Easy to apply OSHA compliant tape for hazard and safety markings.

- Extremely long wear.
- Resists abrasion and solvents.



Improve worker comfort and safety. Reduce leg and back fatigue!

3M™ Safety-Walk™ Cushion Matting 3270E (UPC: 00-048011-34826-1)

- Ergonomic work safety matting that helps reduce worker fatigue.
- Ergonomic matting can increase worker comfort and productivity.
- Light weight for easy moving and repositioning.



Seal ducts and plenums. Maximize efficiency in HVAC systems!



Scotch® Foil Tape 3326, Silver (UPC: 00-051131-85494-9) *Minimize air leaks in HVAC systems by sealing duct joints, insulation and blower compartments.*

- Maximize efficiency in HVAC systems.
- Minimize air leaks in HVAC systems.
- · Help reduce heating and cooling costs.



Alternatives to rivets, bolts, screws and welds. High-Strength bond can replace metal fasteners!

3M™ VHB™ Heavy Duty Mounting Tape 5952 Black

(UPC: 00-051115-25522-9)

Fasten without using rivets, screws or welds.Reclosable plastic storage container keeps tape clean.

• Replaces screws and studs for various permanent mounting applications.

• Attaches to a variety of wall surfaces.



Starter History

Maintain moving parts and lifts. One product - five uses!

3M[™] 5-Way Penetrant

(UPC: 00-021200-21305-2) Silicone free formulation penetrates, Iubricates, de-moisturizes, cleans and prevents rust and corrosion.

Great for loosening rusted or frozen bolts.

• Undercuts grit and grime.




Quick repairs and cleanup. Clean removal, leaves no residue!

3M™ Performance Plus Duct Tape 8979 (UPC: 00-021200-56468-0)



Performance grade duct tape for indoor and outdoor use.
Removes cleanly with no residue from most opaque surfaces for up to six months after it's applied.

• For permanent or temporary applications.



Clean up grease and oil. No-rinse, food grade acceptable cleaner!

3M[™] Citrus Base Adhesive Remover

(UPC: 00-021200-49048-4) Cuts through most adhesive films, labels, grease, grime, tar and oil.

- Effective, non-corrosive, citrus base non-solvent formula.
- · Convenient and portable aerosol dispensing.
- Restricted in California.



۲

Maintain electrical components. Professional's choice!



Scotch® Super 33+ Vinyl Electrical Tape

- (UPC: 00-054007-06132-8)
- All-weather vinyl electrical insulating tape. • Made in the U.S.A.
- Stays put in harsh conditions and extreme temperatures.
- Stretches to conform to any shape.



dels

3M Products



Contain drips and spills. For use as a boom, pillow, pad or roll!



3M[™] Maintenance Sorbent Folded M-FL550DD

(UPC: 50-051131-07172-3) Absorbs most non-aggressive liquids, including oils, coolants, cutting fluids, aqueous-based liquids and petroleum-based products.

 Quicker and easier to dispose of versus granules • Each roll absorbs 31.5 gallons of liquid.







Scotch® Linerless Rubber Splicing Tape 130C

(UPC: 00-054007-41717-0) Protects electrical connections and splices against moisture and heat buildup. · Excellent thermal dissipation properties, even when stretched.

UPC Number

Adhesive

wood and hardboard.

00-021200-82618-4

Linerless self-bonding splice.



Adhesive DP8010

3M[™] Scotch-Weld[™] Structural Plastic 3M[™] Rubber & Vinyl 80 Spray Adhesive

Neoprene-based contact adhesive in aerosol form. It has exceptional resistance to plasticizing oils. Bonds rubber and supported vinyls better than many typical bulk neoprene contact adhesives.

Size

24 oz

3M[™] Super 77[™] Multipurpose

attaching foils, carpeting, lightweight foams, paper,

High tack, high coverage and fast drying for permanently

cardboard, felt and cloth to painted or unpainted metals,

Two-part acrylic-based adhesive (10:1 ratio by volume) that can bond many low surface energy plastics, including many grades of polypropylene, polyethylene, and TPO's without special surface preparation. It has a long (up to 10 minutes) open time and good work life (up to 2 hours). To dispense use 3M™ EPX 10:1 plunger and 10:1 mixing nozzles.

| UPC Number | Size | Color | Case Qty | Units |
|-------------------|-------|-----------|----------|-------|
| 00-021200-49110-8 | 35 mL | Off-White | 12 | EA |

3M[™] Scotch-Weld[™] Low Odor Acrylic Adhesive DP810 Duo-Pak

Toughened structural adhesive with less odor than most acrylic adhesives. Has excellent shear and peel strength along with good impact resistance and durability. Quickly bonds most metals, ceramics, wood

and most plastics.



UPC Number 00-021200-31310-3 00-021200-49077-4

Color Size 1.7 oz Tan 50 mL Black

Case Qty 12 12

ΕA ΕA

00-021200-21210-9

Size 24 fl oz 16.75 oz

Net Weight

Case Qty

Units

CN

Units Case Qty

CN

12

44

Units UPC Number

3M[™] Hi-Strength 90 Spray Adhesive

High strength, fast contact-like adhesive. Fast contact strength buildup for many decorative laminates.



UPC Number 00-021200-30023-3

Net Weight 24 fl oz 17.6 oz

Size

Case Qtv 12

3M[™] Pressure Sensitive Spray Adhesive **Blue 72 Adhesive**

It permits wide-area bonds to be made hours after spraying and easy repositioning of bonds. Provides strong bonds for adhering plastic, foam padding, carpet backing, polyethylene, polypropylene and many other materials to fiberglass, plastics, and particle board.



CN

UPC Number Size **Case Qty** Units 00-021200-30025-7 24 oz CN 12



3M[™] Adhesive Remover

3M[™] Adhesive Remover bites in and dissolves the sticky overspray of many aerosol adhesives, plus grease, oil, grime, tape residue, tar, wax, and more.

UPC Number Size Case Qty Units 00-021200-49048-4 24 07 CN

3M[™] Silicone Lubricant

Dries fast to eliminate squeaks, prevent sticking, and seal out moisture, protecting against rust and corrosion. Preserves plastic, rubber and leather. It prolongs machine and cutting tool life by helping to prevent glue, wax, ink and paint buildup. Does 101 tasks. The silicone polymer is effective between -28°F and 350°F. Adheres to parts exceptionally well, reducing reapplication. Ingredients FDA listed. Comes with a handy snorkel tube for small, hard-to-reach areas.

| UPC Number | Size | Case Qty | Units |
|-------------------|-------|----------|-------|
| 00-021200-30025-7 | 24 oz | 12 | CN |

Scotch[®] Premium Vinyl Electrical Tape Super 88

Scotch® Super 88 Premium Vinyl Electrical Tape offers better mechanical/abrasion resistance, and is thicker for guicker buildup. For professional use, this 8.5 mil tape combines the flexibility of a PVC backing with excellent electrical insulating properties to provide primary electrical insulation for splices up to 600V and protective jacketing. UL Listed and CSA Units Certified. Excellent resistance to UV ravs.



abrasion, moisture, copper corrosion, alkalis and acids. Excellent all-weather performance in cold to 0°F (-18°C) or hot to 221°F (105°C).

| UPC Number | Size | Case Qty | Units |
|-------------------|----------|----------|-------|
| 00-054007-06143-4 | ³∕₄"x66' | 20 | RL |

Scotch[®] Super 33+[™] Vinyl Electric Tape

Scotch[®] Super 33+[™] Vinyl Electric Tape, a black, 7 mil tape, on a 1" core, combines the flexibility of a PVC backing with excellent electrical insulating properties to provide primary electrical insulation for splices up to 600V. Abrasion, corrosion, and UV-resistant, it makes an excellent protective jacketing for high-voltage cables and wire harnessing. UL Listed and CSA Certified, it resists alkalis and acids, and is flame-retardant. Excellent allweather performance in cold to 0°F (-18°C) or hot to 221°F (105°C).

| UPC Number | Size | Case Qty | Units | * base three attents * base three attents * When the transition |
|-------------------|----------|----------|-------|---|
| 00-054007-06130-4 | ³∕₄"x20' | 100 | RL | S. 9 |
| 00-054007-10075-1 | ³∕₄"x44' | 100 | RL | 101030 |
| 00-054007-06133-5 | ³⁄₄"x52' | 100 | RL | |
| 00-054007-06132-8 | ³∕₄"x66' | 20 | RL | |

Scotch[®] Super 33+D Vinyl Electrical **Tape Dispenser Pack**

A premium grade vinyl electrical insulating tape, its aggressive adhesive and elastic backing ensure easy, water-resistant conformation to irregular surfaces in low temperatures, yet will not ooze or melt in high temperatures.



UPC Number 00-054007-10216-8

100 RL



Scotch[®] Vinyl Electrical Tape 35

Identify wires, leads, splices and terminations. Abrasion and weather resistant 7 mil tape. Excellent mechanical and electrical insulation properties. Wraps smoothly and holds tightly over a wide range of temperatures. Mark safety areas. UL listed. CSA approved.



| UPC Number | Size | Color | Case Qty | Units |
|-------------------|----------|--------|----------|-------|
| 00-054007-10836-8 | ³∕₄"x66' | Blue | 100 | RL |
| 00-054007-10885-6 | ³∕₄"x66' | Brown | 100 | RL |
| 00-054007-00072-3 | ³∕₄"x66' | Gray | 100 | RL 0 |
| 00-054007-10851-1 | ³∕₄"x66' | Green | 100 | RL |
| 00-054007-10869-6 | ³∕₄"x66' | Orange | 100 | RL |
| 00-054007-10810-8 | ³∕₄"x66' | Red | 100 | RL |
| 00-054007-11271-6 | ³∕₄"x66' | Violet | 100 | RL |
| 00-054007-10828-3 | ³∕₄"x66' | White | 100 | RL |
| 00-054007-10844-3 | ³∕₄"x66' | Yellow | 100 | RL |
| | | | | |

Scotch[®] Linerless Rubber Splicing Tape 130C



Scotch® Linerless Rubber Splicing Tape 130C is high voltage, insulating, thermally conductive and self-bonding. Typical applications include primary electrical insulation for splicing all solid dielectric cables through 69kV.

| UPC Number | Size | Case Qty | Units |
|-------------------|----------|----------|-------|
| 00-054007-41717-0 | ³⁄₄"x30' | 24 | RL |
| 00-054007-41753-8 | 1"x30' | 24 | RL |
| 00-054007-41718-7 | 1½"x30' | 12 | RL |
| 00-054007-41754-5 | 2"x30' | 12 | RL |

Scotch[®] Rubber Splicing Tape 23

This is a highly conformable, selffusing Ethylene Propylene Rubber (EPR) base highinsulating voltage tape. Comes on an easy release liner.



UPC Number Case Qty Size Units 00-054007-13061-1 1"x20' 100 RL

Scotch[®] Self-Fusing Silicone Rubber **Electrical Tape 70**

This is a high-temperature, arc- and trackresistant tape composed of self-fusing, inorganic silicone rubber with an easy-tear and easy-strip liner.



| UPC | Number |
|--------|-------------|
| 00-054 | 1007-15603- |

Size 1"x30

3M[™] Clean-Walk Mat 5830

An adhesive-coated mat that is used in removing dirt from the bottom of shoes, wheels or any passing objects. To expose an adhesive surface, just peel the top sheet back.



| | | | UPC Number | | Size | Color | Case Qty | Units |
|----|----------|-------|-------------------|------|---------|-------|----------|-------|
| е | Case Qty | Units | 00-021200-55730-9 | 5830 | 18"x36" | White | 4 | CA |
| ∩' | 50 | RI | | | | | | |

3M[™] Glass Cloth Electrical Tape 27

Insulate hot spots. Provides heat-stable insulation for switches, oven and furnace controls and motor leads. 7 mil tape with pressure sensitive adhesive. Thermosetting and heat stable to 266°F. (Class B temperatures) CSA Certified for 130°F and UL Recognized Component listing for 150°F.



| UPC Number | Prod. ID | Size | Case Qty | Units |
|-------------------|----------|-----------|----------|-------|
| 00-054007-27478-0 | 27 | 1½"x60yds | 24 | RL |

Scotch[®] Glass Cloth Tape 69

This is a 7 mil woven glass cloth tape with a silicone pressure sensitive adhesive. Thermosetting and heat stable to 356°F. UL Recognized 180°C. Printable. Sold on a 1" core.



| UPC Number | Size | Color | Case Qty | Units |
|-------------------|----------|-------|----------|-------|
| 00-054007-09910-9 | ³∕₄"x66' | White | 50 | RL |

3M[™] Temflex[™] Friction Tape 1755

Buy this versatile friction tape when you need to protect connections or bundle cables and wires. Thicker than vinyl or glass cloth tape. Splice connections with abrasion resistant cotton tape that has insulating rubber adhesive. Designed to provide protection against abrasion and cutthrough.



Units RL



Scotch[®] Transparent High Performance Duct Tape

Scotch® Transparent Duct Tape virtually

disappears when applied, making repairs

less obvious. This product resists drying,

3M[™] Clean-Walk Framed Mat 5840

An adhesive-coated mat that is used in removing dirt from the bottom of shoes, wheels or any passing objects. To expose anadhesive surface, just peel the top sheet back.

Size

30"x24'



UPC Number 00-021200-55723-1

UPC Number

00-021200-55722-4

Prod ID Size 5840

1

Units

CA

Units

CA

Units CA



Units

CA

Color 311/2"x251/2" White/White

White

3M[™] Clean-Walk Replacement Pad 5842 Color

cracking, and peeling from the damaging effects of UV rays in sunlight.



Units RL

۲

3M[™] Corded Foam Ear Plug 1110



The comfortable fit of soft foam ear plugs with the convenience of a cord. Recommended for moderate to high noise (up to 100 dBA TWA). NRR 29 dB*.

Case Qty

2

 *The NRR may overestimate the protection provided during typical use. 3M recommends reducing the NRR by 50% for estimating the amount of noise reduction provided.

UPC Number Prod. ID 50-051138-29009-7 1110

Case Qtv 500

3M[™] Foam Ear Plug 1110



Soft, comfortable and unobtrusive hearing protection. Recommended for moderate to high

noise (up to 100dBA TWA). NRR 29 dB*.

 *The NRR may overestimate the protection provided during typical use. 3M recommends reducing the NRR by 50% for estimating the amount of noise reduction provided.

1000

UPC Number Prod. ID **Case Qty** 50-051138-29008-0 1100

3M[™] Value Duct Tape 1900

Utility cloth duct tape. Typical physical and performance properties include, adhesion to steel: 58 oz./in. width, tensile strength: 16 lbs/ in width, elongation at break: 12%, thickness: 5.8 mils, temperature use range: up to 200°F 93°C.



| UPC Number | Size | Color | Case Qty |
|-------------------|-------------|--------|----------|
| 00-051115-23421-7 | 1.88"x50yds | Silver | 24 |
| 00-051115-23422-4 | 2.83"x50yds | Silver | 12 |

| 3M ™ | Multi-Pur | pose Duct | Таре | 3900 |
|-------------|-----------|-----------|------|------|
|-------------|-----------|-----------|------|------|

Polyethylene coated cloth with rubber adhesive. Economy grade duct tape. A good choice for general maintenance, repair holding poly carpet and other materials, secures PVC pipes, protects surfaces from abrasion.



| UPC Number | Size | Color | Case Qty | Units |
|-------------------|------------|--------|----------|-------|
| 00-021200-49833-6 | 48mmx54.8m | Black | 24 | RL |
| 00-021200-49832-9 | 48mmx54.8m | Blue | 24 | RL |
| 00-021200-49831-2 | 48mmx54.8m | Olive | 24 | RL |
| 00-021200-49830-5 | 48mmx54.8m | Red | 24 | RL |
| 00-051131-06976-3 | 48mmx54.8m | Silver | 24 | RL |
| 00-021200-49829-9 | 48mmx54.8m | White | 24 | RL |
| 00-021200-49828-2 | 48mmx54.8m | Yellow | 24 | RL |

3M[™] Performance Plus Duct Tape



8979 is designed for both permanent and temporary applications both indoors and outdoors. 8979 provides clean removal with little or no adhesive residue from most opaque surfaces up to 6 months after application. It offers sunlight UV resistance for up to 1-Year without the backing deteriorating or delaminating. Typical physical and performance characteristics include: thickness: 13 mils, adhesion to steel:52 oz, in width, tensile strength: 36 lbs. in width, elongation at break: 21%,temperature use range: Up to 200°F (93°C).

| | UPC Number | Size | Color | Case Qty | Units |
|-------|-------------------|------------|------------|----------|-------|
| | 00-048011-53851-8 | 48mmx22.8m | Slate Blue | 12 | RL |
| | 00-021200-56468-0 | 48mmx54.8m | Slate Blue | 24 | RL |
| | 00-048011-53920-1 | 12"x60yds | Slate Blue | 2 | RL |
| | 00-048011-53919-5 | | Slate Blue | 1 | RL |
| Units | 00-048011-53916-4 | 48mmx54.8m | Olive | 24 | RL |
| RL | 00-048011-53918-8 | 48mmx54.8m | Black | 24 | RL |
| RL | | | | | |

UPC Number

8979

Prod. ID Size 00-051131-83260-2

1.88"x20yds 2120 12

Case Qty



3M[™] Heavy Duty Duct Tape 3939



Construction strength duct tape. Polyethylene coated cloth backing with rubber adhesive. Holds securely, sticks and stays in place. Ideal for moisture sealing, holding poly sheeting for containment and abatement and other tough protection job sites.

UPC Number Size 00-051131-06975-6 48mmx54.8m **Case Qty** 24

Units

RL

Hard-to-Stick Surfaces 2060 This tape features very high adhesion designed specifically for use with lacquer

Scotch[®] Painters' Masking Tape for

coatings. It sticks aggressively, making it ideal for rough surfaces such as stucco, concrete and wood. This tape is for interior and exterior use and can be cleanly removed for up to three days.



Units RL

3M[™] Performance Plus Duct Tape 8979N

Color

Silver



High Performance Duct Tape Nuclear Grade. 00-021200-71132-9 24mmx55m A unique construction of high tensile cloth and aggressive adhesive. Designed for applications in the shipbuilding, nuclear power plant and stainless steel industries. Sunlight/ UV Resistance for up to 6 months.

| UPC Number | Size | Color | Case Qty | Units |
|-------------------|------------|-------|----------|-------|
| 00-048011-53914-0 | 48mmx54.8m | Red | 24 | RL |

Scotch[®] High Performance Masking **Tape 232**

A high performance paper masking tape to be used in the medium temperature paint bake operation. 250°F (121°C).



| UPC Number | Size | Color | Case Qty | Units |
|-------------------|----------|---------|----------|-------|
| 00-021200-02854-0 | 24mmx55m | Natural | 36 | RL |
| 00-021200-04240-9 | 48mmx55m | Natural | 24 | RL |

Scotch[®] General Purpose Masking Tape 234

A very high temperature resistant tape for use in masking and holding applications where temperatures reach 250°F (121°C) for up to 1 hour. A general purpose paper masking tape designed to be used in medium temperature paint bake operation.



| UPC Number | Size | Color | С |
|-------------------|----------|---------|---|
| 00-021200-02982-0 | 24mmx55m | Natural | |
| 00-021200-04244-7 | 48mmx55m | Natural | |

ase Qtv 36 24

UPC Number Size Color Green

Case Qty 36

3M[™] Paper Masking Tape 2209

A general purpose paper tape for holding, bundling, sealing, non-critical masking and a vast number of other jobs where a pressuresensitive tape is needed.



UPC Number Size Color 00-051115-24804-7 24mmx55m Natural 00-051115-24807-8 48mmx55m Natural

Case Qty 36 24

Units RL RL

Scotch[®] Box Sealing Tape 373

Polypropylene tape for single and double wall cartons with high value contents. Rubber resin adhesive instantly seals with more than 8,000 minutes adhesion. Tensile strength of 30 lb/in in machine direction; 60 lb/in cross direction.



| UPC Number | Size | Color | Case Qty | Units |
|-------------------|----------|-------|----------|-------|
| 00-021200-72368-1 | 48mmx50m | Clear | 36 | RL |
| 00-021200-72390-2 | 72mmx50m | White | 24 | RL |

Scotch[®] Box Sealing Tape Dispenser H180

Portable, lightweight, easy to operate hand held tape dispenser. Accommodates up to a 60 yard roll of tape and up to 2" wide. It features an adjustable tape brake allowing control of

tension and delivery

| | y. | | |
|-------------------|------|----------|-------|
| UPC Number | Size | Case Qty | Units |
| 00-021200-96818-1 | 2" | 40 | EA |

48

Units

RL

RL

Scotch[®] Filament Tape 898



High performance. Polypropylene backing reinforced with continuous glass yarn with stain resistant finish. Typical 380 lb/in width tensile strength with aggressive high shear adhesive for heavy duty closure, reinforcing, and banding.

| UPC Number | Size | Color | Case Qty | Units |
|-------------------|----------|-------|----------|-------|
| 00-051131-06896-4 | 12mmx55m | Clear | 72 | RL |
| 00-051131-06898-8 | 24mmx55m | Clear | 36 | RL |
| 00-021200-39869-8 | 48mmx55m | Clear | 24 | RL |

3M[™] Aluminum Foil Tape 425

3M[™] Aluminum Foil Tape 425, dead-soft aluminum foil backing, excellent heat and light reflection to protect against high temperatures and U.V. degradation. The foil also serves as an excellent barrier against moisture, dust, flame, and certain chemicals as used in aircraft paint stripping masking. Acrylic adhesive supplies superior temperature, U.V. and solvent resistance. It provides excellent age life and is ideal for harsh, longterm outdoor environments. Meets F.A.R 25.853(a),

O447



Units RL RL RL

Scotch[®] Foil Tape 3311

21/2"x60yds

4"x60yds



00-021200-60599-4

00-021200-83419-6

Ideal for general duct sealing and MRO repair applications. Shorter roll is designed for use in tight duct work spaces. Meets UL 723 standard.

12

UPC Number 00-051131-85493-2

Size Color 2"x50yds Silver

Case Qty Units RL

12

3M[™] Damping Foil 2552

3M[™] Damping Foil Tape 2552 helps damp vibrations on metal and plastic surfaces vibrating at their natural (resonant) frequency, consists of a pressure-sensitive viscoelastic polymer and aluminum foil constraining layer that effectively converts vibrational energy to negligible heat to reducing irritating noises and decreasing wear and tear on parts. Optimal temperature range from 32°F to 140°F (0°C to 60°C).



UPC Number Color Units Size Case Qty 00-021200-38395-3 2"x36yds Silver 5 RI

Scotch[®] Foil Tape 3326

Scotch® Foil Tape 3326, Ideal for sealing fiberglass duct work and flexible duct systems. Meets UL 181 A/B-FX Standard.



UPC Number Size Color Case Qty 00-051131-85494-9 21/2"x60yds Silver 12

3M[™] Anti-Slip/Anti-Stick Tape 5461

High friction roller tape. Unique rubber backing allows web to release easily from the roll for easy clean up, while still providing a friction surface which allows for the traction needed to drive and guide the web.



RL

| UPC Number | Size | Case Qty | Units |
|-------------------|----------|----------|-------|
| 00-021200-26835-9 | 1"x18yds | 12 | RL |
| 00-021200-24884-9 | 2"x18yds | 6 | RL |

3M[™] Cloth Gaffers Tape 6910



A vinyl coated cloth tape for use in the entertainment industry as "gaffers" tape where light reflection is a concern Matte finish.

| UPC Number | Size | Color | C |
|-------------------|------------|-------|---|
| 00-051131-06843-8 | 48mmx54.8m | Black | |

Case Qty Units 24 RI



3M Products

3M[™] VHB[™] Heavy Duty Outdoor/Indoor Mounting Tape 5952

A very conformable foam that bonds and seals simultaneously to withstand vibration, impact and weathering.



UPC Number 00-051115-25522-9

Size Color 3⁄4"x15yds Black

Case Qty Units RL

12

3M[™] Vinyl Tape 471


3M[™] Vinyl Tape 471, ideal for masking, wrapping or sealing many curved or irregular surfaces, excellent for many lane and safety marking applications, ideal for color coding, abrasion protection, decoration and splicing applications. Meet requirements of CID-A-A-1689.



| UPC Number | Size | Color | Case Qty | Units |
|-------------------|------------|--------|----------|-------|
| 00-021200-61192-6 | ¼"x36yds | Blue | 144 | RL |
| 00-021200-03105-2 | 1⁄2"x36yds | Red | 72 | RL |
| 00-021200-03121-2 | 1"x36yds | Blue | 36 | RL |
| 00-021200-03107-6 | 1"x36yds | Red | 36 | RL |
| 00-021200-04308-6 | 2"x36yds | Blue | 24 | RL |
| 00-021200-04313-0 | 2"x36yds | Green | 24 | RL |
| 00-021200-04312-3 | 2"x36yds | Orange | 24 | RL |
| 00-021200-04305-5 | 2"x36yds | Red | 24 | RL |
| 00-021200-04311-6 | 2"x36yds | White | 24 | RL |
| 00-021200-04310-9 | 2"x36yds | Yellow | 24 | RL |

3M[™] Hazard Marking Vinyl Tape 766

A general purpose hazard marking vinyl tape for use in non-critical applications. Can be used to mark equipment pinch points, and temporary floor marking around equipment or spills.



| UPC Number | Size | Color | Case Qty | Units |
|-------------------|----------|--------------|----------|-------|
| 00-021200-43181-4 | 2"x36yds | Black/Yellow | 24 | RL |

3M[™] Lane Marking Applicator M-77

Dispenser on wheels. Use to apply tape while walking along area to be marked. Use with lane marking tapes such as 3M[™] Vinyl Tape 471 and 3M[™] Safety Stripe Tape 5700 and 5702 in rolls up to 4" x 36vds.



UPC Number 00-021200-12951-3 **Case Qty**

Units ΕA

Janitorial Supplies



۲

*



51

Janitorial Supplies

Jumbo Roll Dispensers







